

6 PIN & SOCKET INSERT



6 Pin & Socket insert

DESCRIPTION

This pair of inserts were designed for increased sturdiness. This helps when mating and assembling under unpredictable conditions. The Stainless Steel cover protects the GRE (Glass Reinforced Epoxy) molding inside from chipping when the inserts come into contact with the housing.

KEY FEATURES

- Stainless Steel cover for protection
- Durable while mating and assembling
- Withstands continuous pressure variation
- Increased reverse-pressure rating

DESIGN RATINGS & TESTING

- Pressure Rating: 2500 psi
- Insulation resistance at sea level: A minimum of 5 Gohms at 500 VDC when tested
- Dielectric withstanding voltage at sea level: with 500 VRMS test voltage, no leakage current in excess of 100 microampere
- Contact strength meets MIL-SPEC requirements

MATERIALS

- GRE (Glass Reinforced Epoxy)
- 316 SST, Passivate per MSBA-009
- Copper & Gold per MSBA-080

QUALITY

- SEACON operate a Quality Management System accredited to ISO 9001:2008.



All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in SEACON standard sales order form. In addition, SEACON reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2014 SEACON
ALL RIGHTS RESERVED