

MOLDED CABLE (AU SERIES)

MICRO SWITCH A033-101-X HALL EFFECT A030-10X

MICRO SWITCH A034-10X A039-10X (6000m) HALL EFFECT A031-10X A032-10X (6000m)

MICRO SWITCH A044-101 (SST) A048-101 (MONEL) O-RING

SEACON PROXIMITY SWITCH

FOR ADDITIONAL INFORMATION SEND REQUEST TO bellvillesales@te.com

MODULAR RIGHT ANGLE WITH MCBH-3M CONNECTOR (NEOPRENE MOLD)

MICRO SWITCH A112-101-X HALL EFFECT A035-10X

MICRO SWITCH A047-10X

MODULAR STRAIGHT WITH MCBH-3M CONNECTOR

MICRO SWITCH A193-101-X (SST) A193-102-X (TI) (7000m)

HALL EFFECT A193-103-X (7000m) REED SENSOR A193-104-X (7000m)

NEOPRENE MOLD OPTIONS

STRAIGHT

RIGHT ANGLE

MODULAR RIGHT ANGLE

AVAILABLE WITH 2 OR 3 WIRE CABLE OR WITH SEACON CONNECTOR OPTIONS: ALL WET, WET-CON AND MICRO WET-CON

MODULAR STRAIGHT WITH GRE CONNECTOR

REED SENSOR A166-101-X (3000m)

FEATURES:

- MICRO SWITCH, 115 VAC/28 VDC, 7 AMP OR 1 AMP MAX RESISTIVE LOAD
- HALL EFFECT, AVAILABLE AS SINKING, RATIOMETRIC (SOURCING) OR LATCHING
- REED SWITCH AVAILABLE AS SHOWN
- HOUSING MATERIAL 316 SST, OPTIONAL MATERIAL TITANIUM AND MONEL
- MOUNTING THREAD 3/4-16 UNF-2A, UNLESS SPECIFIED OTHERWISE
- TYPICAL 3600 METER OPERATING DEPTH, WITH OPTIONS TO 7000m
- CUSTOM DESIGNS AVAILABLE
- X= CONFIGURATION OPTIONS

FOR REFERENCE ONLY

COPYRIGHT© SEACON ADVANCED PRODUCTS LLC

SEACON ADVANCED PRODUCTS LLC

1321 NELIUS RD. - BELLVILLE, TEXAS - 77418

UNDERWATER SWITCH SALES DRAWING

SIZE	CAGE NO. 4EAN5	DWG NO.	REV
B	---	A130-104-1	A
DO NOT SCALE DRAWING		SCALE 3:5	SOLIDWORKS SHEET 1 OF 6