

ITEM	QTY	PART/DESCRIPTION	NOTES	
1	-	INSERT FACE PATTERN	* 11	
2	1	O-RING	* 6	* 13
3	AR	O-RING	* 6	
4	1	MIN-BCR	* 1	* 13
5	1	MIN-CIR	* 2	
6	AR	CONTACT PINS	* 3	* 11
7	1	SPIROLOX	* 5	
8	1	BULKHEAD HEX NUT (OPTIONAL)	* 5	
9	1	BULKHEAD WASHER (OPTIONAL)	* 5	
10	AR	EPOXY (OPTIONAL)	* 7	
11	AR	HOOK-UP WIRE (OPTIONAL PIGTAILS)	* 8	
12	1	MIN-FCR	* 1	* 13
13	1	O-RING	* 6	
14	4	SOCKET CAP HEX SCREW (OPTIONAL)	* 5	
15	1	MIN-CCR	* 1	
16	AR	FILL COMPOUND REQUIRED	* 14	
17	1	MIN-CCP/CCR FI BOOT (OPTIONAL)	* 4	* 12
18	AR	OVERMOLD (OPTIONAL)	* 4	* 12
19	2	NYLON CABLE TIE (OPTIONAL)	* 12	
20	1	MIN-CCP	* 1	* 13
21	1	MIN-CIP	* 2	
22	AR	CONTACT SOCKETS	* 3	* 11
23	1	RETAINING RING	* 5	
24	1	O-RING	* 6	* 13
25	1	O-RING	* 6	
26	1	SPIROLOX	* 5	
27	1	ENGAGING NUT	* 10	
28	2	ENGAGING NUT WASHER	* 9	
29	1	MIN-DSR/MIN-DSRL	* 1	
31	1	MIN-DSP/MIN-DSPL	* 1	
33	1	MIN-PSR/MIN-PSRL	* 9	
35	1	MIN-PSP/MIN-PSPL	* 9	
37	1	MIN-CCP-PBOF-FWD END	* 1	
38	1	MIN-CCP-PBOF-AFT END	* 1	
39	1	MIN-CCP-PBOF-R/A AFT END	* 1	
40	1	O-RING	* 6	
41	3	8-32 UNC-2A HEX SOCKET SET SCREW/CUP POINT	* 5	
42	1	10-24 UNC-2A SLOTTED PAN HEAD SCREW WITH O-RING	* 5	
43	1	MIN-BCR DUAL O-RING	* 1	* 13
44	1	O-RING	* 6	
45	1	O-RING	* 6	* 13
46	1	MIN-CCR-PBOF	* 1	

NOTES:

- * 1 MATERIAL: 316 STAINLESS STEEL PER ASTM A 484.
- * 2 MATERIAL: GLASS REINFORCED EPOXY, SEACON XS-2748.
- * 3 MATERIAL: COPPER ALLOY & GOLD PLATE PER ASTM B 488.
- * 4 MATERIAL: NEOPRENE MOLDING PER SEACON X-5727.
- * 5 MATERIAL: HIGH GRADE STAINLESS STEEL.
- * 6 MATERIAL: NITRILE (FORMERLY KNOWN AS BUNA N).
- * 7 MATERIAL: EPON 828/CIBA 840.
- * 8 MATERIAL: TEFLON® (REGISTERED TRADEMARK FOR DUPONT) TYPE E.
- * 9 MATERIAL: ACETAL PER ASTM D 4181, BLACK.
- * 10 MATERIAL: COPPER ALLOY 630 PER ASTM B 150.
- * 11 REFERENCE FACE CONFIGURATIONS FOR SIZE OF CONTACTS AND LOCATIONS.
- * 12 AN OVERMOLD OR FIELD INSTALLABLE BOOT IS OPTIONAL ON BOTH THE CCP AND THE CCR.
- * 13 DOVETAIL GROOVE TO PREVENT LOSS OF O-RING.
- * 14 NOT SUPPLIED.