



SEACON Optical Subsea Umbilical Termination Assembly (oSUTA)

ADVANCED TECHNOLOGY

- Dual chamber design
- Pressure balanced oil filled (PBOF) chamber on the connector side with MKII interface
- Atmosphere chamber on the cable side, with ports for seal integrity testing
- Integral fiber management system in both chambers
- Modular design with options for umbilical cable and multi-hose exits
- Field Installable (no compounds)
- Dual seals on all barriers

DEEP WATER CAPABILITY

- Operational depth of 4,000m (max)
- Operational temperature from -5°C to +45°C
- Design life up to 25 years

TE Connectivity (TE)'s SEACON oSUTA is a termination and distribution unit for optical distribution systems. The design features a fiber management system, mechanical armor termination and high pressure fiber optic penetrators between the connector and cable chambers.

TE Components . . . TE Technology . . . TE Know-how . . .
AMP | AGASTAT | CII | HARTMAN | KILOVAC | MICRODOT | NANONICS | POLAMCO | Raychem
SEACON | Rochester | DEUTSCH

Empower Engineers to Solve Problems, Moving the World Forward.

SEACON Optical Subsea Umbilical Termination Assembly

STANDARDS AND SPECIFICATIONS

- **Design Life:** 25 Years
- **Operational Depth:** 4,000m (max)
- **Operational Temperature:** -5°C to +45°C
- **Storage Temperature:** -20°C to +60°C
- **Compensation Fluid:** Silicone Oil

QUALIFICATION TESTING

- **Hyperbaric pressure testing to 450 bar**
(4000m water - depth +10%)
- Helium seal verification testing via test port feature
- Environmental Stress Screening (ESS) testing
- Thermal cycling under pressure
- **Axial Load Testing:**
 - **Inline:** 5000N
 - **90°:** 2500N
 - Drop Test
- **Qualified according to:**
 - Statoil TR1232, TR1233 & TR2390
 - Total GS EP SPS 019 & GS EP SPS 021
 - ISO 13628-6

OPTICAL PERFORMANCE

- **Maximum Splice Insertion Loss:** <0.05dB
- **Maximum Penetrator Insertion Loss:** < 0.2dB
- **Maximum Connector Insertion Loss:** < 0.5dB
- **Maximum Overall SUTA Insertion Loss:** < 0.8dB
- **Typical Overall SUTA Insertion Loss:** < 0.5dB
- **Ultra Physical Contact connector Return Loss:** <-30dB
- **Angled Physical Contact connector Return Loss:** <-45dB

CONFIGURATIONS

- **Standard:**
 - 2-32 off Fiber Optic Circuits: Single-Mode or Multi-Mode
 - The SUTA can be designed for most fiber optic cables.
Please contact TE's SEACON for details.

MATERIALS

- **Standard:**
 - **Shell:** Titanium CP Gr. 2
 - **Seals:** Nitrile
- **Optional**
 - **Shell:** 316L Stainless Steel
 - **Seals:** Fluoroelastomer



seaconworldwide.com

© 2017 TE Connectivity. All Rights Reserved.

04/17 Rev 1

SEACON, SEACON (logo), DEUTSCH, Rochester Cable, TE, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity family of companies.

Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.

North America +1 800 522 6752 • EMEA +800 0440 5100 • Asia Pacific +86 400 820 6015 • Japan 044 844 8180 • Visit te.com for additional country contacts.