

SEACON

SEACON ADVANCED PRODUCTS, LLC PRODUCT DATASHEET

MODULAR PROXIMITY SWITCHES



Modular Proximity Switch

DESCRIPTION

SEACON offers a variety of Switches. This Modular Proximity Switch utilizes many of our proven proximity switches and integrates them with a SEACON Micro WET-CON, underwater pluggable connector.

Installation has never been easier. Once the switch is mounted the cable can easily be added. Because a wet pluggable connector is used, this can be done in any conditions, even submerged.

As a result of this modular design, switches become interchangeable. Simply replace the cable and the switch can be used elsewhere. This is particularly useful when taking spares to sea.

KEY FEATURES

- Hermetically sealed
- No o-rings or gaskets
- Single Pole Double Throw
- Reinforced Neoprene Mold
- Integrated Underwater Pluggable connector incorporating MC-BH-3M

QUALITY

- SEACON Advanced Products, LLC operate a Quality Management System certified to ISO 9001:2008, ISO 14001:2004 and OHSAS 18001:2007.





SEACON ADVANCED PRODUCTS, LLC PRODUCT DATASHEET

CONFIGURATIONS

AU-VM Series, AU-VME Series.

- | | |
|---------------------------|--|
| Standard Proximity - | The switch can be normally open or closed. When a magnet is presented the switch will either open or close the circuit. |
| Sinking Hall Effect - | The sensor is normally closed. When a magnet is present the sensor opens at a very high rate of speed. |
| Ratiometric Hall Effect - | The switch is normally open and will gradually close as the magnet is brought closer to the switch. This is ideal for lining up two objects. |
| Latching Hall Effect - | The circuit is closed when a South magnet is present and opens when a North magnet is presented. |
- Mounting type:
 - Standard 3/4" - 16 UNF
 - Molded available for all series

DESIGN RATINGS & TESTING

- Pressure rating:
 - 6,000 psi - All series
 - 10,000 psi - VME 10k
- Power load:
 - Light duty = 1 amp - Available for all series
 - Standard duty = 7 amps - Available for all series
- Standard Temperature range: -40° to +175°F available for all series

QUALIFICATIONS

- Proximity Switch meets NAVSEA 5162424-102-11
- Micro Switch design to MIL-S-8805

PRINCIPLE OF OPERATION

A **Modular Proximity Switch** uses magnets, either in attraction or repulsion, to open or close an electrical circuit. Except for hall effect, all switches are single pole double throw.

All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in **SEACON** standard sales order form. In addition, **SEACON** reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2015 **SEACON** Advanced Products, LLC.
ALL RIGHTS RESERVED

