



SEACON PRODUCT DATASHEET

MODULAR HIGH DENSITY 12 CHANNEL ELECTRO / OPTIC INSERT(S)



Modular high density 12 channel Electro/Optic insert(s)

DESCRIPTION

The high-density modular connector inserts were developed for the U.S. Navy on a SBIR (Small Business Innovative Research) contract. The 12-channel connectors can be populated in any combination of electrical or optical contacts. Optical contacts available in PC and APC. Single and multi-mode compatible.

KEY FEATURES

- Mated Length: 2.12"
- Overall Diameter: 0.625"
- Suitable for **MSS** and **MINI-CON** series of dry-mate-able connectors
- Depth Rating: • 2,500 psi survival
• 1,250 psi operational
- Electric rating: 2.5 A @ 500V
- Modular: Mix and match electrical and optical contacts

DESIGN RATINGS & TESTING

- Optical Insertion Loss: < -0.5dB per channel @ 1550 nM
- Back reflection: • <-40dB (PC)
• < -70dB (APC)
- Mate/De-mate Testing: >500 cycles
- Isopar Compatible

MATERIALS

- 6AL-4V Titanium insert bodies
- 316 Stainless Steel Fiber Optic Contacts

QUALITY

- **SEACON** operate a Quality Management System accredited to ISO 9001:2008.



All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in **SEACON** standard sales order form. In addition, **SEACON** reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2014 **SEACON**
ALL RIGHTS RESERVED