

# PRODUCT NEWS

## OPTI-CON SERIES PRESSURE RATINGS

As part of our continuous improvement process the **SEA CON**® Group consistently reviews it's product ranges through both customer feedback and internal improvements. It is via these processes that **SEA CON**® identified the potential for a design clarification to the **OPTI-CON** connector range.

CONNECTOR	CABLE VERSION		PBOF VERSION	
	STAINLESS STEEL	TITANIUM	STAINLESS STEEL	TITANIUM
<b>OPT-F-SINGLE WAY</b>	1,500 psi	1,500 psi	7,500 psi	7,500 psi
<b>OPT-G-4 WAY</b>	7,500 psi	7,500 psi	7,500 psi	7,500 psi
<b>OPT-M-8 WAY</b>	7,500 psi	7,500 psi	7,500 psi	7,500 psi
<b>OPT-Q-12 WAY</b>	2,000 psi	7,500 psi	2,000 psi	7,500 psi
<b>OPT-T-20 WAY</b>	2,000 psi	7,500 psi	2,000 psi	7,500 psi

### NOTES

- The minimum length for a PBOF hose is 3 meters. Shorter lengths will incur an extra charge due to a higher manufacturing attrition rate.
- Pressure ratings for cable versions are dependent on cable.

The current literature will be updated with this information shortly.

