

**SEACON**®

UNDERWATER ELECTRICAL AND FIBER OPTIC CONNECTORS



# SWITCHES

HIGH INTEGRITY UNDERWATER SWITCHES

**SEACON**  
advanced  
PRODUCTS

## PRODUCT DATASHEET

# HIGH INTEGRITY UNDERWATER SWITCHES

### LIMIT SWITCHES

- Hermetically sealed
- Pressure rated up to 6,000 psi
- Rated for > 50,000 cycles
- Load capacities; 1 and 7 amps
- Single pole, double throw
- Stainless Steel or Titanium
- Non-metal options available
- Refer to datasheet SAPL-DS-0020



### PLASTIC LIMIT SWITCHES

- Rated for > 50,000 cycles
- Pressure rated up to 500 feet (152 meters)
- Load capacities; 1 and 7 amps
- Single pole, double throw
- Black Acetal (Delrin® - DuPont trademark for Acetal Resin)
- Refer to datasheet SAPL-DS-0021



### POSITIVE ACTION SWITCHES

- Hermetically sealed
- Pressure rated up to 6,000 psi
- Rated for > 50,000 cycles
- Load capacities; 1 and 7 amps
- Single pole, double throw
- Stainless Steel or Titanium
- Refer to datasheet SAPL-DS-0022



### PROXIMITY SWITCHES

- Hermetically sealed
- Pressure rated up to 6,000 psi
- Rated for > 50,000 cycles
- Load capacities; 1 and 7 amps
- Standard proximity and hall effect
- Stainless Steel or Titanium
- Proximity switch meets NAVSEA requirements for part number 5162424-101-11
- Magnet retainer meets NAVSEA requirements for part number 5062424-102-11
- Refer to datasheet SAPL-DS-0023



## PRODUCT DATASHEET

### MODULAR PROXIMITY SWITCHES

- Hermetically sealed
- No o-rings or gaskets
- Pressure rated up to 6,000 psi
- Rated for > 50,000 cycles
- Load capacities; 1 and 7 amps
- Standard proximity and hall effect
- Manufactured to NAVSEA requirements
- Incorporates MC-BH-3M connector
- Reinforced Neoprene mold
- Refer to datasheet SAPL-DS-0024



### SEACON ADVANCED PRODUCTS, LLC - SWITCHES

SEA CON® manufacture a full line of hermetically sealed limit switches, proximity switches, potentiometers and magnetic couplings. In addition to this SEA CON® is able to offer a range of plastic switches and has also developed a proximity switch utilizing it's connector technology.

All switches are qualified for successful deployment on Submarines, ROV's, AUV's, UUV's, hulls, submersibles of all types, buoys, underwater communication systems, surveillance devices, oceanographic equipment, on deck and wherever equipment is exposed to severe marine and other hostile environments. These switches are also used in oil well logging, well head controls, dredging, fishery gates, and underwater Christmas Trees.

SEA CON® switches are USED ALL OVER THE WORLD and our corporate philosophy emphasizes flexibility, responsiveness, staying ahead of market requirements, quality assurance and service after sale.

The SEA CON® Group has an extensive and comprehensive agency network able to supply our full range of products which covers every continent or area across the globe. To find a representative in your area please contact our sales department or refer to our catalogue.

### QUALITY

- SEACON Advanced Products, LLC operate a Quality Management System certified to ISO 9001:2008.



All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in SEA CON® standard sales order form. In addition, SEA CON® reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2011 SEACON Advanced Products, LLC.  
ALL RIGHTS RESERVED

SEACON Advanced Products, LLC.

1321 Nelius Road, PO Box 767, Bellville, Texas 77418, USA

TEL: +1 (979) 865 8846 FAX: +1 (979) 865 8859

E-Mail: sales@seacon-ap.com Website: www.seacon-ap.com

SAPL-DS-0025

ADVANCED PRODUCTS

Rev 6

Page 2 of 2

## PRODUCT DATASHEET

# LIMIT SWITCHES



*Limit Switches*

## DESCRIPTION

SEACON® offers a variety of Limit Switches to meet demanding needs. Limit Switches are designed to give a signal to a control system when a moving component like an overhead door or piece of machinery has reached the end point (or limit) of its travel or just a specific point of its journey.

## KEY FEATURES

- Load capacities
  - Light duty (LD - 1 amp)
  - Standard Duty (SD - 7 amps)
- AU series switches are rated to 6,000 psi (4000 m) and available in LD and SD

## MATERIALS

- 316 Stainless steel - AU, AU-LSW, AU-LS 10K
- Titanium - AU, WT-90, AU-LS 10K, AU-LSW

## QUALITY

- SEACON Advanced Products, LLC operate a Quality Management System certified to ISO 9001:2008.



**SEACON Advanced Products, LLC.**

1321 Nelius Road, PO Box 767, Bellville, Texas 77418, USA

TEL: +1 (979) 865 8846 FAX: +1 (979) 865 8859

E-Mail: sales@seacon-ap.com Website: www.seacon-ap.com

SAPL-DS-0020

LIMIT SWITCHES

Rev 5

Page 1 of 2

## PRODUCT DATASHEET

### CONFIGURATIONS

- AU Series, WT-90, AU-LSW, AU-LS 10K.  
Mounting type:
  - 3/4" - 16 UNF for AU
  - Molded cable available for all series
  - Oil filled cable available for AU series

---

### DESIGN RATINGS & TESTING

- Pressure Rating:
  - 6,000 psi - AU, WT-90 and AU-LSW
  - 10,000 psi - AU-LS 10K
- Power load:
  - Light Duty = 1 amp (115 VAC/28 VDC)
  - Standard Duty = 7 amps (115 VAC/28 VDC)
- Minimum cycles: All series greater than 50,000
- Button options: Large (1.5 in), Medium (.65 in), Small (.375 rad.) - Available for AU and WT-90 series 1.5 and .375
- Standard temperature range: -65° to +400°F available for AU, WT-90, AUL-SW and AU-LS 10K

---

### OPERATION

- Full stroke of Plunger:
  - AU series and WT-90 - 0.4 in. (10.2 mm)

---

### PRINCIPLE OF OPERATION

A **Limit Switch** uses a mechanism moving against a spring to move a magnet which is then placed either in attraction or repulsion, to open or close an electrical circuit. All switches are single pole double throw.

All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in **SEA CON**® standard sales order form. In addition, **SEA CON**® reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2010 **SEACON** Advanced Products, LLC.  
ALL RIGHTS RESERVED

## PRODUCT DATASHEET

# PLASTIC LIMIT SWITCHES



*Plastic Limit Switch*

### DESCRIPTION

SEACON® has developed various forms of Switches. This Limit Switch is ideally suited for diver applications. Rated to 500 feet (152 meters), this durable switch fits nicely into a gloved hand. Originally designed as a push to talk button, this switch has a wide variety of uses.

The switch is made of durable Black Acetal (ASTM D418, POM111 or 211). It is available in either light (1 amp) or standard duty (up to 7 amps).

### KEY FEATURES

- Black Acetal (Delrin® - (DuPont trademark for Acetal Resin)) Construction
- Single Pole Double Throw
- Available in light and standard duty
- Load capacities;
  - Light duty (LD - 1 amp)
  - Standard duty (SD - 7 amps)

### QUALITY

- SEACON Advanced Products, LLC operate a Quality Management System certified to ISO 9001:2008.



Certificate No. 6936

**SEACON Advanced Products, LLC.**

1321 Nelius Road, PO Box 767, Bellville, Texas 77418, USA

TEL: +1 (979) 865 8846 FAX: +1 (979) 865 8859

E-Mail: sales@seacon-ap.com Website: www.seacon-ap.com

SAPL-DS-0021

PLASTIC LIMIT SWITCHES

Rev 3

Page 1 of 2

## PRODUCT DATASHEET

### MATERIALS

- Black Acetal (Delrin®) ASTM D4181, POM111 OR 211
- 

### CONFIGURATIONS

- Part number AU-PLS-(LD or SD)-C
- 

### DESIGN RATINGS & TESTING

- Pressure rating: 500 feet (152 meters)
  - Power load:
    - Light duty = 1 amps (115 VAC/28 VDC)
    - Standard duty = 7 amps (115 VAC/28 VDC)
  - Minimum cycles: Greater than 50,000
- 

### OPERATION

- Full Stroke of Plunger: 0.30 inches

All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in SEA CON® standard sales order form. In addition, SEA CON® reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2010 SEACON Advanced Products, LLC.  
ALL RIGHTS RESERVED

## PRODUCT DATASHEET

# POSITIVE ACTION SWITCHES



*Positive Action Switches*

### DESCRIPTION

SEA CON® offers a variety of Switches, including Positive Action Switches to meet the demanding needs of our customers.

Positive Action Switches are designed to give a continuous signal when the switch is activated. Various configurations are available including Rotary and Push and Pull (Kill Switches).

### KEY FEATURES

- Load capacities
  - Light duty (LD - 1 amp)
  - Standard Duty (SD - 7 amps)
- Hermetically sealed
- 316 Stainless Steel or Titanium
- AU series switches are rated to 6,000 psi (4,000 m) and available in LD and SD
- Single Pole Double Throw

### MATERIALS

- 316 Stainless steel - AU, AU-LSW, AU-LS 10K
- Titanium - AU, AU-LS 10K, AU-LSW

### QUALITY

- SEACON Advanced Products, LLC operate a Quality Management System certified to ISO 9001:2008.



**SEACON Advanced Products, LLC.**

1321 Nelius Road, PO Box 767, Bellville, Texas 77418, USA

TEL: +1 (979) 865 8846 FAX: +1 (979) 865 8859

E-Mail: sales@seacon-ap.com Website: www.seacon-ap.com

SAPL-DS-0022

POSITIVE ACTION SWITCHES

Rev 5

Page 1 of 2

## PRODUCT DATASHEET

### CONFIGURATIONS

AU Series.

- Mounting type:
  - 3/4" - 16 UNF for AU
  - Bulkhead available for AU series
  - Cable moulding and PBOF options available

---

### DESIGN RATINGS & TESTING

- Pressure Rating:
  - 6,000 psi - AU and AU-LSW
  - 10,000 psi - AU-LS 10K
- Power load:
  - Light Duty = 1 amp (115 VAC/28 VDC) - Available for all series
  - Standard Duty = 7 amps (115 VAC/28 VDC) - Available for all series
- Button options: Large (1.5 in), Medium (.65 in), Small (.375 rad.) - Available for AU and LS 1.5 and .375.
- Standard temperature range: -65° to +400°F available for AU, AUL-SW and AU-LS 10K
- Minimum cycles: All series greater than 50,000

---

### OPERATION

- Switches incorporate Detent features

---

### PRINCIPLE OF OPERATION

A **Positive Action Switch** uses a mechanism (Rotary or Linear) to move a magnet which is then placed either in attraction or repulsion, to open or close an electrical circuit. All switches are single pole double throw.

All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in **SEA CON**® standard sales order form. In addition, **SEA CON**® reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2010 **SEACON** Advanced Products, LLC.  
ALL RIGHTS RESERVED

## PRODUCT DATASHEET

# PROXIMITY SWITCHES



*Proximity Switches*

### DESCRIPTION

**SEACON**® offers a variety of Switches. The **Proximity Switch** uses magnets, either in attraction or repulsion, to open or close an electrical circuit. Several types are available to meet customer's needs. All switches are single pole double throw.

### KEY FEATURES

- Load capacities
  - Light duty (LD - 1 amp)
  - Standard Duty (SD - 7 amps)
- Hermetically sealed
- No O-rings or Gaskets
- Single Pole Double Throw
- No O-rings or Gaskets
- **Proximity Switch** meets NAVSEA requirements for part number 5162424-101-11
- Magnet Retainer meets NAVSEA requirements for part number 5062424-102-11

### MATERIALS

- 316 Stainless Steel - Available for all series
- Titanium - Available for all series

### QUALITY

- **SEACON** Advanced Products, LLC operate a Quality Management System certified to ISO 9001:2008.



**SEACON** Advanced Products, LLC.

1321 Nelius Road, PO Box 767, Bellville, Texas 77418, USA

TEL: +1 (979) 865 8846 FAX: +1 (979) 865 8859

E-Mail: sales@seacon-ap.com Website: www.seacon-ap.com

SAPL-DS-0023

PROXIMITY SWITCHES

Rev 6

Page 1 of 2

## PRODUCT DATASHEET

### CONFIGURATIONS

AU-VM Series, AU-VME Series.

Standard Proximity -	The switch can be normally open or closed. When a magnet is presented the switch will either open or close the circuit.
Sinking Hall Effect -	The sensor is normally closed. When a magnet is present the sensor opens at a very high rate of speed.
Sinking/Sourcing Hall Effect -	The switch is normally open and will gradually close as the magnet is brought closer to the switch. This is ideal for lining up two objects.
Latching Hall Effect -	The circuit is closed when a South magnet is present and opens when a North magnet is presented.

---

### DESIGN RATINGS & TESTING

- Pressure rating:
  - 6,000 psi - VM-series, VME series.
  - 10,000 psi - VME series.
- Power load:
  - Light duty = 7 amps (115 VAC/28 VDC) - Available for all series
  - Standard Duty = 7 amps (115 VAC/28 VDC) - Available for all series
- Minimum cycles: All series greater than 50,000
- Standard Temperature range: -65° to +400°F available for VM and VME series

---

### OPERATION

- Magnets in repulsion for AU

---

### QUALIFICATIONS

- Proximity Switch meets NAVSEA requirements for part number 5162424-101-11
- Magnet Retainer meets NAVSEA requirements for part number 5062424-102-11

---

### PRINCIPLE OF OPERATION

A Proximity Switch uses magnets, either in attraction or repulsion, to open or close an electrical circuit. Except for hall effect, all switches are single pole double throw.

All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in SEA CON® standard sales order form. In addition, SEA CON® reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2010 SEACON Advanced Products, LLC.  
ALL RIGHTS RESERVED

## PRODUCT DATASHEET

# MODULAR PROXIMITY SWITCHES



*Modular Proximity Switch*

### DESCRIPTION

SEA CON® offers a variety of Switches. This Modular Proximity Switch utilizes many of our proven proximity switches and integrates them with a SEA CON® Micro WET-CON, underwater plugable connector.

Installation has never been easier. Once the switch is mounted the cable can easily be added. Because a wet plugable connector is used, this can be done in any conditions, even submerged.

As a result of this modular design, switches become interchangeable. Simply replace the cable and the switch can be used elsewhere. This is particularly useful when taking spares to sea.

### KEY FEATURES

- Hermetically sealed
- No O-rings or gaskets
- Single Pole Double Throw
- Reinforced Neoprene Mold
- Integrated Underwater Plugable connector incorporating MC-BH-3M

### QUALITY

- SEA CON Advanced Products, LLC operate a Quality Management System certified to ISO 9001:2008.



**SEA CON Advanced Products, LLC.**

1321 Nelius Road, PO Box 767, Bellville, Texas 77418, USA

TEL: +1 (979) 865 8846 FAX: +1 (979) 865 8859

E-Mail: sales@seacon-ap.com Website: www.seacon-ap.com

SAPL-DS-0024

MODULAR PROXIMITY SWITCHES

Rev 3

Page 1 of 2

## PRODUCT DATASHEET

### CONFIGURATIONS

AU-VM Series, AU-VME Series, BU-VM Series.

- |                                |  |
|--------------------------------|--|
| Standard Proximity -           | The switch can be normally open or closed. When a magnet is presented the switch will either open or close the circuit.                      |
| Sinking Hall Effect -          | The sensor is normally closed. When a magnet is present the sensor opens at a very high rate of speed.                                       |
| Sinking/Sourcing Hall Effect - | The switch is normally open and will gradually close as the magnet is brought closer to the switch. This is ideal for lining up two objects. |
| Latching Hall Effect -         | The circuit is closed when a South magnet is present and opens when a North magnet is presented.   |
- Mounting type:
    - Standard 3/4" - 14 NPSM-2A (nominal OD 1in) - for all sizes. Bulkhead available for BU series.
    - Molded available for all series

---

### DESIGN RATINGS & TESTING

- Pressure rating:
  - 6,000 psi - All series.
  - 10,000 psi - VME series
- Power load:
  - Light duty = 1 amp - Available for all series
  - Standard duty = 7 amps - Available for all series
- Standard Temperature range: -65° to +150°F - Available for all series

---

### QUALIFICATIONS

- Proximity Switch meets NAVSEA 5162424-102-11
- Micro Switch design to MIL-S-8805

---

### PRINCIPLE OF OPERATION

A **Modular Proximity Switch** uses magnets, either in attraction or repulsion, to open or close an electrical circuit. Except for hall effect, all switches are single pole double throw.

All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in **SEA CON**® standard sales order form. In addition, **SEA CON**® reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2010 **SEACON** Advanced Products, LLC.  
ALL RIGHTS RESERVED

**SEACON ADVANCED PRODUCTS, LLC**

1321 Nelius Road, P.O. Box 767,  
Bellville, Texas 77418, USA.  
TEL: +1 (979) 865-8846  
FAX: +1 (979) 865-8859  
E-Mail: sales@seacon-ap.com  
Website: www.seacon-ap.com

**SEACON BRAZIL**

Rua Conde de Bonfim 120 sala 212,  
Tijuca, Rio de Janeiro,  
Brazil, CEP: 20520-053.  
TEL: +55 (21) 8849-3336  
E-Mail: renata@seacon-ap.com

**SEA CON®**

1700 Gillespie Way,  
El Cajon, California 92020, USA.  
TEL: +1 (619) 562-7071  
FAX: +1 (619) 562-9706  
E-Mail: seacon@seaconworldwide.com  
Website: www.seaconworldwide.com

**SEA CON US GULF AREA SALES OFFICE**

21925 Franz Road, Suite 401,  
Katy, Texas 77449, USA.  
TEL: +1 (281) 599-3509  
FAX: +1 (281) 599-3517  
E-Mail: gulfcoastsales@seaconworldwide.com  
Website: www.seaconworldwide.com

**SEA CON US EAST COAST SALES OFFICE**

50 Airport Road,  
Westerly, RI 02891, USA.  
TEL: +1 (401) 348-0155  
FAX: +1 (401) 348-0227  
E-Mail: eastcoastsales@seaconworldwide.com  
Website: www.seaconworldwide.com

**SEA CON FLORIDA SALES OFFICE**

Building B, Suite 22,  
3959 South Nova Road,  
Port Orange,  
Florida 32127, USA.  
TEL: +1 (281) 802-5504  
E-Mail: steven.thumbbeck@seacon-ap.com

**SEACON (europe) LTD**

Seacon House, Hewett Road,  
Gapton Hall Industrial Estate,  
Great Yarmouth, Norfolk, NR31 0RB, UK.  
TEL: +44 (0) 1493-652733  
FAX: +44 (0) 1493-652840  
E-Mail: sales@seaconeurope.com  
Website: www.seaconeurope.com

**SEA CON GLOBAL PRODUCTION**

Callejon Terrazos #8, Local 2-C,  
Las Brisas 1ra. Seccion,  
Tijuana, B.C., Mexico C.P. 22610.  
TEL: +52 (664) 626-2726  
FAX: +52 (664) 686-8922  
E-Mail: sales@seaconglobal.com  
Website: www.seaconglobal.com  
Dial from U.S.A. TEL: +1 (619) 308-7901  
TOLL FREE: (888) 562-7072  
FAX: +1 (619) 308-7900

**SEACON PHOENIX, LLC.**

15 Gray Lane, Suite 108,  
Hopkinton Industrial Park,  
Ashaway, RI 02804, USA.  
TEL: +1 (401) 637-4952  
FAX: +1 (401) 637-4953  
E-Mail: sales@seaconphoenixllc.com  
Website: www.seaconphoenixllc.com

All reasonable efforts have been taken to ensure that the information contained herein is accurate at the date of publication, but no representation or warranty as to the accuracy or completeness of such information is intended or to be implied by its inclusion herein. Any and all representations and warranties pertaining to the information and products referred to herein shall be set forth in SEA CON® standard sales order form. In addition, SEA CON® reserves the right to make changes to the contents hereof without notice, therefore it is suggested that at the time of inquiry, the appropriate sales office or factory be contacted directly for verification of published specifications and products availability.

© 2011 SEACON Advanced Products, LLC

ALL RIGHTS RESERVED

